




 <b>16</b> <b>INLES d.d.</b> Kolodvorska 22 SI-1310 Ribnica SLOVENIJA	
<b>INO-KF Living MD – 01</b> IN11431/0  <b>EN 14351-1:2006+A1:2010</b>  <b>Single casement PVC window</b>  for build in vertical wall openings of the buildings without resistance to fire	
Air permeability Watertightness Resistance to wind load Thermal transmittance $U_w$	to class - <b>C3/B3</b> to class - <b>9A</b> class - <b>4</b> <b>1,2 W/m<sup>2</sup>K</b>
notified Body: IFT Rosenheim GmbH Theodor-Gietl Str. 7-9 83036 Rosenheim, Germany (NB-Nr. 0757)	

 <b>16</b> <b>INLES d.d.</b> Kolodvorska 22 SI-1310 Ribnica SLOVENIJA	
<b>INO-KF Living MD – 06</b> IN11431/1  <b>EN 14351-1:2006+A1:2010</b>  <b>Double casement PVC window (symmetric)</b>  for build in vertical wall openings of the buildings without resistance to fire	
Air permeability Watertightness Resistance to wind load Thermal transmittance $U_w$	to class - <b>C3/B3</b> to class - <b>9A</b> class - <b>4</b> <b>1,2 W/m<sup>2</sup>K</b>
notified Body: IFT Rosenheim GmbH Theodor-Gietl Str. 7-9 83036 Rosenheim, Germany (NB-Nr. 0757)	


 <b>16</b> <b>INLES d.d.</b> Kolodvorska 22 SI-1310 Ribnica SLOVENIJA	
<b>INO-KF Living MD – 07</b> IN11431/2  <b>EN 14351-1:2006+A1:2010</b>  <b>Double casement PVC window (asymmetric)</b>  for build in vertical wall openings of the buildings without resistance to fire	
Air permeability Watertightness Resistance to wind load Thermal transmittance $U_w$	to class - <b>C3/B3</b> to class - <b>9A</b> class - <b>4</b> <b>1,2 W/m<sup>2</sup>K</b>
notified Body: IFT Rosenheim GmbH Theodor-Gietl Str. 7-9 83036 Rosenheim, Germany (NB-Nr. 0757)	


 <b>16</b> <b>INLES d.d.</b> Kolodvorska 22 SI-1310 Ribnica SLOVENIJA	
<b>INO-KF Living MD – 08</b> IN11431/3  <b>EN 14351-1:2006+A1:2010</b>  <b>Fixed PVC window</b>  for build in vertical wall openings of the buildings without resistance to fire	
Air permeability Watertightness Resistance to wind load Thermal transmittance $U_w$	to class - <b>C3/B3</b> to class - <b>9A</b> class - <b>4</b> <b>1,2 W/m<sup>2</sup>K</b>
notified Body: IFT Rosenheim GmbH Theodor-Gietl Str. 7-9 83036 Rosenheim, Germany (NB-Nr. 0757)	

 <b>16</b> <b>INLES d.d.</b> Kolodvorska 22 SI-1310 Ribnica SLOVENIJA	
<b>INO-KF Living MD – 11</b> IN11431/5  <b>EN 14351-1:2006+A1:2010</b>  <b>single casement PVC balcony door</b>  for build in vertical wall openings of the buildings without resistance to fire	
Air permeability Watertightness Resistance to wind load Thermal transmittance $U_w$	to class - <b>C3/B3</b> to class - <b>9A</b> class - <b>4</b> <b>1,2 W/m<sup>2</sup>K</b>
notified Body: IFT Rosenheim GmbH Theodor-Gietl Str. 7-9 83036 Rosenheim, Germany (NB-Nr. 0757)	

 <b>16</b> <b>INLES d.d.</b> Kolodvorska 22 SI-1310 Ribnica SLOVENIJA	
<b>INO-KF Living MD – 12</b> IN11441/6  <b>EN 14351-1:2006+A1:2010</b>  <b>double casement PVC balcony door (symmetric)</b>  for build in vertical wall openings of the buildings without resistance to fire	
Air permeability Watertightness Resistance to wind load Thermal transmittance $U_w$	to class - <b>C3/B3</b> to class - <b>9A</b> class - <b>4</b> <b>1,2 W/m<sup>2</sup>K</b>
notified Body: IFT Rosenheim GmbH Theodor-Gietl Str. 7-9 83036 Rosenheim, Germany (NB-Nr. 0757)	

\* This value refers to the glazing with  $U_g = 1,1 \text{ W/m}^2\text{K}$ .

 <b>16</b> <b>INLES d.d.</b> Kolodvorska 22 SI-1310 Ribnica SLOVENIJA	
<b>INO-KF Living MD – 13</b> IN11441/7  <b>EN 14351-1:2006+A1:2010</b>  <b>double casement PVC</b> <b>balcony door (asymmetric)</b>  for build in vertical wall openings of the buildings without resistance to fire  Air permeability <b>to class - C3/B3</b> Watertightness <b>to class - 9A</b> Resistance to wind load <b>class - 4</b> Thermal transmittance $U_w$ <b>1,2 W/m<sup>2</sup>K*</b>	
notified Body: IFT Rosenheim Gmbh Theodor-Gietl Str. 7-9 83036 Rosenheim, Germany (NB-Nr. 0757)	


 <b>16</b> <b>INLES d.d.</b> Kolodvorska 22 SI-1310 Ribnica SLOVENIJA	
<b>INO-KF Living MD – 14</b> IN11441/8  <b>EN 14351-1:2006+A1:2010</b>  <b>sliding PVC balcony door</b> <b>(PSK)</b>  for build in vertical wall openings of the buildings without resistance to fire  Air permeability <b>to class - C3/B3</b> Watertightness <b>to class - 9A</b> Resistance to wind load <b>class - 4</b> Thermal transmittance $U_w$ <b>1,2 W/m<sup>2</sup>K*</b>	
notified Body: IFT Rosenheim Gmbh Theodor-Gietl Str. 7-9 83036 Rosenheim, Germany (NB-Nr. 0757)	

\* This value refers to the glazing with  $U_g = 1,1 \text{ W/m}^2\text{K}$ .